

## PH-5L Stud Welding Gun





The PH-5L stud welding gun allows shear connectors to be welded on metallic workpieces at lightning speed.



## PH-5L SOYER drawn arc stud welding gun with ceramic ferrule equipment

**Description:** 

The newly developed, robust and ergonomically designed PH-5L stud welding gun is especially suitable for larger stud diameters from 16 mm onwards, welded in series production at high continuous welding sequences under hardest conditions and requirements. A new type of manual oil damping system regulates the plunging speed, which is absolutely necessary when stud diameters of ≥ 12 mm are applied. Due to the high energy demand required with larger stud diameters, the welding cable has been strengthened to 95 mm² and is separately guided by means of a special holder. Together with easy and practical operation, the PH-5L stud welding gun offers a maximum of technical performance features for producing high-quality stud welding joints. (For innovative special features, please see over).

Technical data:

Welding range:

Material:

Welding and control cables: Total length with ceramic ferrule equipment:

Total height above grip:

Total width: Weight:

Studs and pins from M6 - M24 and/or Ø 6 - 22 mm (25 mm)

Steel, stainless steel and heat-resistant steel

5 m highly flexible

approx. 350 mm up to approx. 560 mm (depending on the length of studs and

support legs)

185 mm 80 mm

2.3 kg without cables and ceramic ferrule equipment

Subject to technical changes

## Innovative Special Features of the PH-5L Stud Welding Gun

The new PH-5L SOYER stud welding gun is a top-line product with precision mechanics and long-term quality. It is mainly used for welding shear connectors and concrete anchors of large diameters. The invariably high-quality performance of this stud welding gun is an important step towards the quality assurance in stud welding processes. All important setting parameters can be easily and rapidly adjusted by hand without requiring any tools.

Additional performance features of the PH-5L stud welding gun include:

- ▶ Development and production are in compliance with all prescribed safety targets such as
  - the latest safety and accident prevention regulations (Act on the Safety of Technical Working Equipment)
  - electromagnetic compatibility (EMC Act)
  - European regulations (EU Directives on Machinery)
- ► Stable, impact- and break-proof whole-body synthetic housing
- ▶ Optimum protection against weld spatters, dirt and other contamination
- Automatic and maintenance-free length compensation system for differing welding stud lengths and positioning conditions
- ▶ New and manually adjustable oil damping system to regulate the plunging speed

- Welding and control cables are fastened as cable bundle to the gun handle and secured against parting of cables by means of a special strain relief
- Easy replacement of the standard baseplate with ceramic ferrule equipment by a baseplate with gas shroud
- ► Easily adjustable support legs for differing stud lengths
- ▶ Fine hand adjustment of lift in defined steps of 0.5 mm by means of a special notched turning knob at the gun's end
- Scale for measuring the lift
- ▶ Spirit level at the gun's end to guarantee vertical welding positions
- ▶ High positioning accuracy owing to backlash-free motional sequences in ball bearings, and long service life owing to high-quality mechanical components

SOYER top-of-the-range products awarded the following prizes for











Quality

Management





